

Produced by: KZWM OGNIOPHON S.A.
ul. Krakowska 83c, 34-120 Andrychów, Poland

Representative for BENELUX: SACO b.v.b.a.
Meeuwenlaan 34, 1640 Sint-Genesius-Rode, tel: +32 2 466 84 20

www.osec.be

OSEC

EXTINGUISHERS

Application

Ideal for car, boat, home & camping protection.
Specifically designed with the vehicle & home market in mind.




Product features

- Rapid application through simple operating elements.
- Ergonomic design for easy one-hand use.
- Test valve behind the pressure gauge for easy maintenance.
- Simple attachment with supplied bracket (plastic or steel).
- Good extinguishing performance.
- Squeeze grip control valve allows total control of discharge.
- Designed for easy service and maintenance.
- Steel cylinder finished in red high quality polyester powder coating.


Quality and safety

Produced and approved in accordance with requirements of European Norm EN3, European Directive PED 97/23/EC and Quality Management Standard ISO 9001.



Technical data

Fire rating	5A 21B C
Volume of agent	1 kg
Working agent	N ₂
Operation time	6 s
Test pressure	25 bar
Working pressure	10 bar
Temperature range	-30 °C / +60 °C
Weight Full Aprox	1,7 kg
Packing in box	10 pcs
Box dimensions	550/230/300 l/w/h
Quantity per pallet	350
Gross weight	635 kg
Net weight	615 kg



1 kg Powder extinguisher

Stored pressure

GP 1x ABC

